

DECLARATION OF CONFORMITY

Manufacturer:

WPM Estonia OÜ
Männiku tee 104 A, 11216 Tallinn

Product:

WPM SEALING ELEMENT 125 L - Art.nr. 0001-02
WPM SEALING ELENET 125 R – Art.nr 0002-03
WPM SEALING ELEMENT 80 R –Art.nr 0002-04
WPM SEALING ELEMENT 125R-PF- Art.nr. 0002-PF
Sealing elements with mineral coating

Specifications:

Steel material: galvanized steel
Steel sheet height: 125 mm / 125 mm / 80 mm
Steel sheet thickness: approx. 0,7 mm
Steel sheet length: 2,5 m / 7,5 m / 7,5 m
Special coating: mineral coating
Thickness of complete sheet: approx. 1,7 mm
Color: silver/grey
Temperature resistance: -35°C - +75°C
Working temperature: no limit

The product has been tested for water tightness at the TTU Institute of Building and Architecture SCIENTIFIC AND TESTING LABORATORY, Test Protocol No 372/19 17.05.2019.

Proven water resistance of 2.5 bar.

Area of application:

WPM Sealing Elements is used for sealing against pressurized water in concrete construction joints for bottom/wall, wall/wall, bottom/bottom and wall/ceiling applications. Typical areas of application are drinking water tanks, areas of changing water levels, cast-in-place concrete and precast unit constructions.

Tallinn, February 10, 2021



Indrek Uusalu
WPM Estonia OÜ
CEO